

DATASHEET

TBK-BUL4745B.2

MAIN FEATURES

HD 4 in 1.
1080P resolution.
5-50 mm varifocal lens.
Sensitivity: 0,01 Lux (F1.2, AGC ON).
6 units of Array Type IR LEDs with 50 m range.
OSD Menu.
IP66.

Bullet camera, with 1080P resolution and 5-50mm varifocal lens (with external adjustment), specially designed for the surveillance of perimeters and specific areas. HD 4 in 1 technology: switchable video signal output provides TVI/AHD/CVI/CVBS signal.





TBK-BUL4745B .2

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.9" SONY CMOS Sensor
Signal System	NTSC/PAL
Effective Pixels	1920(H) x 1080(V)
Electronic Shutter	AUTO/ 1/50 (1/60) -1/50,000sec
Min. Illumination	0.01Lux (F1.2, AGC ON)
Video Frame Rate	PAL/NTSC: 1080p@25/30fps
Video Output	AHD / TVI / CVI / CVBS
CAMERA FEATURES	
S/N Ratio	>41dB
Noise Reduction	2D&3D DNR
Day&Night	Color / B&W/ AUTO / EXT
White Balance	Auto / Manual/Indoor/Outdoor
OSD Language	English / Chinese / German / French / Italian / Spanish / Polish / Russian / Portuguese / Dutch / Turkish / Korean / Japanese
AGC	Auto
IR LED	6pcs Array LED
IR Range	50M
LENS	
Focal Length	5-50mm Manual Zoom Lens
Angle of View	H: 42.1°~6.3°
Mount Type	Φ14
GENERAL	
Operating Conditions	-40 °C to 50 °C, humidity: 90% or less (non-condensation)
Power Supply	12 VDC <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
Power Consumption	Max. 10W
Protection Level	IP66
Material	Metal
IR Range	Up to 50 m
Communication	Up the coax (TVI output)
Dimensions	103 mm × 83 mm × 278 mm
Weight	Approx. 1188 g